



EMPTY ENCLOSURE

RK 4/50-L



Unfortunately no illustration

RK 4/50-L

Empty enclosure

CUSTOMIZABLE

360 x 254 x 111 mm
Article number: 61695001

Terminal block enclosure, Polystyrene, light grey, similar to RAL 7035, incl. 18 attachment bushes M20, seal range 8 - 13.5 mm, IP54, 4 attachment bushes M25, seal range 9 - 18.5 mm, 2 attachment bushes M32, Seal range 11 - 23 mm, 1 attachment bush M40, seal range 17 - 30 mm

without terminals, with NS 35



Technical data

Measures

Width:	360 mm
Length:	254 mm
Height:	111 mm

Material

Base:	Polystyrene, light grey, similar to RAL 7035
Cover:	Polystyrene, light grey, similar to RAL 7035
Sealing:	Polyurethane
Cover screw:	Polyamide 6, fiber-glass reinforced

Accessory

- ASS-gro - External hinge set
- KS M25-gro - Combi set
- HBA - Mounting material
- KS M20 - Combi set
- KS M25 - Combi set
- KS M32 - Combi set
- TK ABL - External fixing lugs kit
- VSG - Padlock kit

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short term):	95%
Max. rel. humidity at 40° C:	50%



EMPTY ENCLOSURE

RK 4/50-L

Other attributes

Ingress protection:	IP66/IP54 - acc. EN60529 / DIN VDE 0470-1
Impact resistance:	IK07 acc. DIN EN 5012 / VDE 0470 Part 100
Protection class:	II - isolate protection acc. VDE 0106
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Combustion behaviour acc. to UL 94:	HB acc. UL94
Combustion behaviour acc. to VDE:	650°C acc. VDE 0471/ EN 60695
Fitted for outdoor application:	No
Cable entries:	Yes
sealable:	Yes
weatherproof:	No
Equipment:	Standard rail NS 35